

# Table of Contents

<b>Case 1</b> .....	1
AddInfo .....	1
Cause .....	1
Solution .....	1

ethercat, 이더넷, panasonic, 파나소닉, unknown, config, 실패, scan

# Unknown Slave

× SCAN 결과 알 수 없는 Slave가 확인됨

## Case 1

**AddInfo**

The screenshot shows the 'Configurator' software interface. At the top, there are buttons for 'Scan', 'Download', 'Upload', 'Save', 'Load', and 'Close'. Below these are tabs for 'Topology', 'Net Info', 'Slave Info', and 'ProcessData'. The 'Topology' tab is active, showing a network diagram with four nodes: '[0200] Master MASTER-DC', '[0001] NONE Unknown', '[0002] NONE Unknown', and '[0003] NONE Unknown'. A red box highlights the 'Net Info' section, which lists three entries: '[0000h] Unknown', '[0000h] Unknown', and '[0000h] Unknown'. At the bottom, there are buttons for 'Index', 'Addr', 'Initial', 'PreOP', 'SafeOP', and 'OP', along with a '+ -' button and a button labeled 'Apply AutoAddress To Servo'.

### Cause

- SCAN 시 참조할 ESI File(\*.xml) 이 없음

### Solution

- XML 폴더 ( .\ComiIDE\Data\XML ) 에 Unknown으로 확인되는 Slave의 XML 파일을 복사<sup>1)</sup>

Category

1)

ECatConfig 사용 시 .\EcatConfig\Data\XML

From:  
<http://comizoa.com/info/> - -

Permanent link:  
[http://comizoa.com/info/doku.php?id=platform:ethercat:1\\_setup:10\\_config:ts:unknown\\_slave&rev=1540520552](http://comizoa.com/info/doku.php?id=platform:ethercat:1_setup:10_config:ts:unknown_slave&rev=1540520552)

Last update: **2024/07/08 18:22**