2025/11/06 16:24 1/1

ESI (xml)

2025/11/06 16:24 1/3

×

•

• .

## ESI (xml)

• 60B9h ~ 60BDh

∘ 60B9h : TouchProbe Status

60BAh : Touch Probe pos1 pos value60BCh : Touch Probe pos2 pos value

• 60BBh (Touch Probe pos1 neg value), 60BDh (Touch Probe pos2 neg value)

2025/11/06 16:24 2/3

```
<Object>
   <Index>#x60B8</Index>
   <Name LcId="1033">Touch probe function</Name>
   <Type>UINT</Type>
   <BitSize>16</BitSize>
   <Info>
        <DefaultValue>0</DefaultValue>
   </Info>
   <Flags>
        <Access>rw</Access>
        <PdoMapping>R</PdoMapping>
   </Flags>
</Object>
<Object>
   <Index>#x60B9</Index>
   <Name LcId="1033">Touch probe status</Name>
   <Type>UINT</Type>
   <BitSize>16</BitSize>
   <Info>
        <DefaultValue>0</DefaultValue>
   </Info>
   <Flags>
        <Access>ro</Access>
        <PdoMapping>T</PdoMapping>
</Object>
<Object>
   <Index>#x60BA</Index>
   <Name LcId="1033">Touch probe pos1 pos value</Name>
   <Type>DINT</Type>
   <BitSize>32</BitSize>
   <Info>
        <MinData>0000080</MinData>
        <MaxData>FFFFFF7F</MaxData>
        <DefaultData>0000000/DefaultData>
   </Info>
    <Flags>
        <Access>ro</Access>
        <PdoMapping>T</PdoMapping>
   </Flags>
</Object>
<Object>
   <Index>#x60BC</Index>
   <Name LcId="1033">Touch probe pos2 pos value</Name>
   <Type>DINT</Type>
   <BitSize>32</BitSize>
   <Tnfo>
        <MinData>00000080</MinData>
        <MaxData>FFFFFF7F</MaxData>
        <DefaultData>0000000/DefaultData>
   </Info>
   <Flags>
        <Access>ro</Access>
       <PdoMapping>T</PdoMapping>
   </Flags>
</Object>
```

2025/11/06 16:24 3/3

From:

http://comizoa.com/info/ - -

 $\label{link:permanent link:http://comizoa.com/info/doku.php?id=platform:ethercat:2_info:10\_touchprobe:10\_support\_check&rev=1564379661$ 

Last update: 2024/07/08 18:22